

VRF R410A VC Max Outdoor Unit

MVC-M450WV2WN1– Cooling Only

3-phase, 220V, 60Hz



Submittal Data

Job name: _____

Location: _____

Tag: _____

Date: _____



MVC-M450WV2WN1 Features:

- ♦ High efficiency by using DC inverter compressor and DC fan motor
- ♦ 1 to 26 indoor units connection
- ♦ Up to 40Pa ESP enables longer duct runs
- ♦ Wide operation range:
cooling -15°C to 55°C (5°F to 131°F)

Specifications:

Model			MVC-M450WV2WN1
Cooling ¹	Capacity	kW (kBtu/h)	45.0 (153.5)
	Input	kW	11.72
	EER	kW/kW	3.84
Connectable indoor unit	Total capacity		50-130% of outdoor unit capacity
	Quantity		26
Compressor	Type		DC inverter
	Quantity		1
Fan motor	Type		DC
	Quantity		1
Outdoor air flow		m ³ /h (CFM)	15600 (9182)
Sound pressure level ²		dB(A)	61
Net dimensions (W×H×D)	mm		940×1760×825
	inch		37-1/64 x 69-19/64 x 32-31/64
Packed dimensions (W×H×D)	mm		1010×1945×890
	inch		39-49/64 x 76-37/64 x 35-3/64
Net/Gross weight		kg (lbs)	200/215 (441/474)
Refrigerant type/factory charge		kg (lbs)	R410A / 8.4 (18.5)
Liquid/Gas pipe		mm(inch)	Φ15.9/Φ28.6 (Φ5/8/Φ1-1/8)
Minimum Circuit Amps (MCA)		A	48.0
Recommended Fuse Size (MFA)		A	63.0

Notes:

1. Indoor temperature 27°CDB, 19°CWB; outdoor temperature 35°CDB; equivalent refrigerant piping length 7.5m with zero level difference.
2. Sound pressure level is measured 1m in front of the unit and 1m above the floor in a semi-anechoic chamber.

Dimensional Drawing:

Unit (mm)

