


FUJITSU
Calidad y Durabilidad

Halcyon 

HI-EFFICIENCY INVERTER FAN COIL

9, 12, 18, 24, 36 and 48 BTU Systems

Systems: ARU09RFL, ARU12RFL, ARU18RFL, ARU24RGLX, ARU36RGLX and ARU48RGLX



ARU09RFL, ARU12RFL AND ARU18RFL UP TO 21.5 SEER

- Inverter Technology
- 4-Way Auto Louver for Balanced Comfort
- Smart System: Auto Mode
- Humidity Control
- Fresh Air Intake
- Wired Remote Controller UTY-RNBYU (optional)



ARU24RGLX, ARU36RGLX AND ARU48RGLX

ARU24RGLX - UP TO 17.5 SEER

ARU36RGLX - UP TO 16.7 SEER

ARU48RGLX - UP TO 16.6 SEER



- Slim & Compact design indoor unit & outdoor unit
- Improved installation flexibility
- Smart System: Auto Mode
- High Efficiency & Quiet operation
- Use WIFI adapter UTY-TFSXZ2 to control your unit with Fujitsu's FGLAir smartphone app




Please complete product registration at www.fujitsugeneral.com to validate your new warranty

OLDACH
REFRIGERATION, AIR CONDITIONING & VENTILATION SUPPLIER


		ARU9RLF	ARU12RLF	ARU18RLF	ARU24RLF
Performance					
Nominal Cooling	BTUh	9,000	12,000	18,000	24,000
Nominal Heating	BTUh	10,200	13,500	20,000	27,000
Fan (Cooling Mode)					
Air Circulation: Hi	CFM (m3/h)	353 (600)	383 (650)	554 (940)	783 (1,330)
Medium	CFM (m3/h)	324 (550)	353 (600)	518 (880)	730 (1,240)
Low	CFM (m3/h)	294 (500)	324 (550)	483 (820)	648 (1,100)
Quiet	CFM (m3/h)	265 (450)	283 (480)	442 (750)	607 (1,030)
Fan Speed Stage		4 + Auto	4 + Auto	4 + Auto	4 + Auto
Sound					
Indoor Level (Clg/Htg): Hi	dB (A)	28/28	29/29	32/33	33/35
Medium	dB (A)	27/26	28/28	31/32	32/34
Low	dB (A)	26/25	27/27	30/31	30/32
Quiet	dB (A)	25/24	26/24	29/29	29/29
Electrical					
Voltage/Frequency/Phase		208 - 230/60/1	208 - 230/60/1	208 - 230/60/1	208 - 230/60/1
Circuit Breaker	W.C	0 ~ 0.36	0 ~ 0.36	0 ~ 0.36	0 ~ 0.36
Current Rated: Cooling	Amps	0.3	0.35	0.44	0.66
Current Rated: Heating	Amps	0.3	0.35	0.44	0.66
Input Power	W	49	58	73	111
Size & Weight					
Net Weight	lbs. kg	41 (19)	41 (19)	50 (23)	59 (27)
Dimensions: Height	inch	7 - 25/32	7 - 25/32	7 - 25/32	7 - 25/32
	mm	198	198	198	198
Width	inch	27 - 9/16	27 - 9/16	35 - 7/16	43 - 5/16
	mm	700	700	900	1,100
Depth	inch	24 - 13/32	24 - 13/32	24 - 13/32	24 - 13/32
	mm	620	620	620	620
Supply Duct Flange Dimensions: Height	inch	5 - 15/16	5 - 15/16	5 - 15/16	5 - 15/16
	mm	151	151	151	151
Width	inch	25 - 19/32	25 - 19/32	33 - 15/32	41 - 11/32
	mm	650	650	850	1,050
Depth	inch	3/4	3/4	3/4	3/4
	mm	19	19	19	19
Return Duct Dimensions: Height	inch	6	6	6	6
Width	inch	22	22	30	37 - 3/4
	mm	559	559	762	959
Depth	inch	3/4 (flat)	3/4 (flat)	3/4 (flat)	3/4 (flat)
	mm	19 (flat)	19 (flat)	19 (flat)	19 (flat)
Refrigerant		R410A	R410A	R410A	R410A

		ARU24RGLX	ARU36RGLX	ARU48RGLX			
Performance							
Nominal Cooling	BTUh	24,000	36,000	48,000			
Min-Max Cooling	BTUh	5,400-29,000	9,600 - 39,000	17,100 - 50,000			
Nominal Heating	BTUh	27,000	36,000	53,000			
Min-Max Heating	BTUh	5,400-32,400	9,200 - 48,000	18,000 - 55,000			
SEER		17.5	16.7	16.6			
HSPF		10.8	11.3	10.3			
EER		12.6	10	10.1			
Cooling Operation Range	°F (°C)	-5 - 115 (-20 - 46)	-5 - 115 (-20 - 46)	-5 - 115 (-20 - 46)			
	°F (°C)	-5 - 75 (-20 - 24)	-5 - 75 (-20 - 24)	-5 - 75 (-20 - 24)			
Moisture Removal	Pt./h (l/h)	4.0 (1.9)	5.3 (2.5)	8.2 (3.9)			
Fan (Cooling Mode)							
Air Circulation (CLG/Htg): Hi	CFM (m3/h)	800 (1360)	1207 (2050)	1501 (2550)			
Medium	CFM (m3/h)	636 (1080)	965 (1640)	1201 (2040)			
Low	CFM (m3/h)	518 (880)	783 (1330)	971 (1650)			
Quiet	CFM (m3/h)	400 (680)	630 (1070)	842 (1430)			
Fan Speed Stage		4 + Auto	4 + Auto	4 + Auto			
Sound							
Indoor Level (Clg/Htg): Hi	Db (A)	35/35	37/35	40/40			
Medium	Db (A)	30/30	33/33	35/35			
Low	Db (A)	28/28	30/30	33/33			
Quiet	Db (A)	24/24	26/26	29/29			
Outdoor Level Clg/Htg	Db (A)	53/55	54/56	57/59			
Electrical							
Voltage/Frequency/Phase		208 - 230/60/1	208 - 230/60/1	208 - 230/60/1			
Circuit Breaker	Amps	30	30	30			
Current Rated: Cooling	Amps	8.3	15.8	20.9			
Current Rated: Heating	Amps	9	12.6	19.5			
Power Use Rated/Max: Cooling	KW	1.90/2.82	3.60/4.00	4.75/5.01			
Power Use Rated/Max: Heating	KW	2.06/2.96	2.88/4.38	4.45/4.77			
Size & Weight							
Net Weight	lbs. (kg)	93 (42)	134 (61)	121 (55)	134 (61)	121 (55)	209 (95)
Dimensions: Height	inch	11 - 13/16	32 - 11/16	11 - 13/16	32 - 11/16	11 - 13/16	32 - 11/16
	mm	300	830	300	830	300	1290
Width	inch	39 - 3/8	35 - 7/16	55 - 1/8	35 - 7/16	55 - 1/8	35 - 7/16
	mm	1000	900	1400	900	1400	900
Depth	inch	27-9/16	13	27-9/16	13	27-9/16	13
	mm	700	330	700	330	700	330
Refrigerant		R410A	R410A	R410A	R410A	R410A	R410A
		Indoor ARU24RGLX	Indoor ARU36RGLX	Indoor ARU36RGLX	Indoor ARU36RGLX	Indoor ARU36RGLX	Indoor ARU36RGLX
		Outdoor AOU24RGLX	Outdoor AOU36RGLX	Outdoor AOU36RGLX	Outdoor AOU36RGLX	Outdoor AOU36RGLX	Outdoor AOU36RGLX



SLIM DUCT

Adaptable when ceiling cavity is small and there is no slope for drain



SLIM DUCT

Built-in drain pump allows for installation of slim duct unit in smaller spaces than traditional units.

